

# SOLANS Protex PE-HD 74 Cable Protection Pipe



Cable protection pipe for laying data and telecommunication cables, power cables, control and signal cables.

## Product information

**Material:** PE-HD new material  
**Standard:** DIN 16874  
**Colour:** Black  
**Labelling:** Standard Solans  
**Delivery unit:** 6-metre length  
**Pipe design:** Smooth inner and outer wall  
**Pipe end:** Chamfered/smooth

## Technical Information

**Sealing system:**  
 SR special lip seal made of SBR with excellent compression behaviour Alternative PVC bonding system.

**Pressure resistance:** (23 +-5)°C, 0,5 bar  
**Installation:** According to DIN EN 1610, KRV Installation Instructions A 535a  
**Pipe statics:** Static calculation on request according to ATV worksheet 127

Upon request, our cable conduits can be customized according to customer's requirements, such as the marking, color, design, labeling, delivery form or even dimensions.

Art.-Nr.	Outer diameter (mm)	Wall thickness (mm)	SDR	Weight (kg/m)	Availability	Pallet pcs/m
090200	50	4,6	11	0,69	A	123/ 738
090205	63	3,6	17,6	0,72	A	88/ 528
090210	75	2,9	26	0,73	A	73/ 438
090215	90	3,5	26	1,03	A	58/ 348
090220	110	3,4	32	1,23	S	48/ 288
090221	110	4,2	26	1,48	S	48/ 288
090222	110	5,3	21	1,82	S	48/ 288
090223	110	6,3	17,6	2,12	S	48/ 288
090230	125	3,9	32	1,59	S	43/ 258
090231	125	4,8	26	1,91	S	43/ 258
090250	160	4,9	33	2,51	S	33/ 198
090251	160	6,2	26	3,10	S	33/ 198
094241	140	6,7	21	4,18	S	38/ 228
094250	160	3,2	50	2,41	A	33/ 198
094251	160	4,7	34	3,44	S	33/ 198

S: Standard programme, A: On request