

SOLANS Protex PE-HD 76 Cable Protection Pipe



Cable protection pipe for laying data and telecommunication cables, power cables, control and signal cables.

Product information

Material: PE-HD Recyclat
Standard: DIN 16876
Colour: Black without stripes
Labelling: Standard Solans
Delivery unit: 6-metre length
Pipe design: Smooth inner and outer wall
Pipe end: Chamfered/smooth

Technical data

Sealing system:
 SR special lip seal made of SBR with excellent compression behaviour

Pressure tightness: (23 +-5)°C, 0.5 bar
Installation: According to DIN EN 1610, KRV Installation instructions A 535a
Pipe statics: Static calculation on request according to ATV worksheet 127

Upon request, our cable conduits can be customized according to customer's requirements, such as the marking, color, design, labeling, delivery form or even dimensions.

Art.-Nr.	Outer diameter (mm)	Wall thickness (mm)	SDR	Weight (kg/m)	Availability	Pallet pcs/m
091200	50	4,6	11	0,69	A	123/ 738
091205	63	3,6	17,6	0,72	A	88/ 528
091210	75	2,9	26	0,73	A	73/ 438
091215	90	3,5	26	1,03	A	58/ 348
091220	110	3,4	32	1,23	S	48/ 288
091221	110	4,2	26	1,48	S	48/ 288
091222	110	5,3	21	1,82	S	48/ 288
091223	110	6,3	17,6	2,12	S	48/ 288
091230	125	3,9	32	1,59	S	43/ 258
091231	125	4,8	26	1,91	S	43/ 258
091250	160	4,9	33	2,51	S	33/ 198
091251	160	6,2	26	3,10	S	33/ 198

S: Standard programme, A: On request