

# SOLANS Protex PP 78 Cable Protection Pipe



Cable protection pipe for laying data and telecommunication cables, power cables, control and signal cables.

## Product information

**Material:** PP Recyclat  
**Standard:** DIN 16878  
**Colour:** Black  
**Labelling:** Standard Solans  
**Delivery unit:** 6-metre length  
**Pipe design:** Smooth inner and outer wall  
**Pipe end:** Chamfered/smooth and marked

## Technical Information

**Sealing system:** SR special lip seal made of SBR  
**Pressure resistance:** (23 +-5)°C, 0,5 bar  
**Installation:** According to DIN EN 1610, KRV Installation Instructions A 535a  
**Pipe statics:** Static calculation on request according to ATV worksheet 127

Upon request, our cable conduits can be customized according to customer's requirements, such as the marking, color, design, labeling, delivery form or even dimensions.

Art.-Nr.	Outer diameter (mm)	Wall thickness (mm)	SDR	Weight (kg/m)	Availability	Pallet pcs/m
092220	110	3,4	32	1,17	S	48/ 288
092221	110	4,2	26	1,40	S	48/ 288
092223	110	5,3	21	1,74	S	48/ 288
092224	110	6,3	17,6	2,12	S	48/ 288
092230	125	3,9	32	1,50	S	43/ 258
092231	125	4,8	26	1,80	S	43/ 258
092250	160	4,9	33	2,40	S	33/ 198
092251	160	6,2	26	3,00	S	33/ 198

S: Standard programme, A: On request