

SOLANS Protex PVC 73 Cable Protection Pipe



Cable protection pipe for laying data and telecommunication cables, power cables, control and signal cables.

Product information

Material: PVC new material
Standard: DIN 16873
Colour: Black without stripes
Labelling: Standard Solans
Delivery unit: 6-metre length
Pipe design: Smooth inner and outer surfaces
Pipe end: Chamfered/smooth and marked

Technical Information

Sealing system:
 SR special lip seal made of SBR with excellent compression behaviour Alternative PVC bonding system

Pressure resistance: (23 +-5)°C, 0,5 bar
Installation: According to DIN EN 1610, KRV Installation Instructions A 535a
Pipe statics: Static calculation on request according to ATV worksheet 127

Upon request, our cable protection pipes can be customized according to customer's requirements, such as marking, color, design, labeling, delivery form or even dimensions.

Art.-Nr.	Außendurchmesser (mm)	Wandstärke (mm)	Gewicht (kg/m)	Verfügbarkeit	Palette Stk./m
093401	50	1,8	4,43	S	123/ 738
093400	50	3,7	0,81	S	123/ 738
093406	63	1,9	0,57	S	88/ 528
093411	75	2,2	0,79	S	73/ 438
093416	90	2,7	1,13	S	58/ 348
093421	110	3,2	1,64	S	48/ 288
093422	110	5,3	2,61	S	48/ 288
093431	125	3,7	2,13	S	43/ 258
093441	140	6,7	4,18	S	38/ 228
093451	160	4,7	3,44	S	33/ 198

S: standard programme, A: on request; *breakthrough pipe without socket