

SOLANS Protex PVC 75 Cable Protection Pipe



Cable protection pipe for laying data and telecommunication cables, power cables, control and signal cables.

Product information

Material: PVC Recyclat
Standard: DIN 16875
Colour: Black without stripes
Labelling: Standard Solans
Delivery unit: 6-metre length
Pipe design: Smooth inner and outer surfaces
Pipe end: Chamfered/smooth and marked

Technical Information

Sealing system:
 SR special lip seal made of SBR with excellent compression behaviour Alternative PVC bonding system

Pressure resistance: (23 +-5)°C, 0,5 bar
Installation: According to DIN EN 1610, KRV Installation Instructions A 535a
Pipe statics: Static calculation on request according to ATV worksheet 127

Upon request, our cable conduits can be customized according to customer's requirements, such as the marking, color, design, labeling, delivery form or even dimensions.

Art.-Nr.	Outer diameter (mm)	Wall thickness (mm)	SDR	Weight (kg/m)	Availability	Pallet pcs/m
094201	50	1,8	28	4,43	S	123/ 738
094200	50	3,7	14	0,81	A	123/ 738
094206	63	1,9	33	0,57	S	88/ 528
094211	75	2,2	34	0,79	S	73/ 438
094216	90	2,7	33	1,13	S	58/ 348
094221	110	3,2	34	1,64	S	48/ 288
094222	110	5,3	21	2,61	A	48/ 288
094231	125	3,7	34	2,13	S	43/ 258
094241	140	6,7	21	4,18	S	38/ 228
094251	160	4,7	34	3,44	S	33/ 198

S: standard programme, A: on request; *breakthrough pipe without socket